



has not been replaced. Please contact your customer care center for more information.

Overview

Model Name	APC Easy UPS On-Line SRV 2000VA 120V
Includes	CD with software , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Argentina , Aruba , Bahamas , Barbados , Belize , Bermuda , Bolivia , Brazil , Cayman Islands , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Grenada , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Paraguay , Peru , Puerto Rico , SAINT KITTS AND NEVIS , SAINT LUCIA , SAINT VINCENT AND THE GRENADINES , Trinidad And Tobago , Uruguay , Venezuela , VIRGIN ISLANDS (UNITED STATES)

Output

Output Power Capacity	1600 Watts / 2000 VA
Max Configurable Power (Watts)	1600 Watts / 2000 VA
Nominal Output Voltage	120V
Output Voltage Distortion	3%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	110, 115V
Crest Factor	3 : 1
Crest Factor	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(4) NEMA 5-20R (Battery Backup)

Input

Nominal Input Voltage	120V
Input Frequency	40 - 70 Hz
Input Connections	NEMA 5-20P
Other Input Voltages	110 , 115

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4 hour(s)

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600 Joules
---------------------	------------

Physical

Maximum Height	238.0 mm
Maximum Width	145.0 mm
Maximum Depth	400.0 mm
Net Weight	17.0 kg
Shipping Weight	18.9 kg
Shipping Height	355.0 mm
Shipping Width	235.0 mm
Shipping Depth	525.0 mm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6 meters
Audible noise at 1 meter from surface of unit	0.000 dB

Conformance

Approvals	CE , IEC 62040-1-1 , IEC 62040-1-2
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs