

# NX-3200/3300

## VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models with 14-pin Universal connector are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.

### FEATURES

- Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols
- NXDN Conventional and Type-C & Gen2 Trunking
- DMR Tier II & Site Roaming
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 5-Line Text Message Frame (3 Lines of Text, icon & key guide)
- 7-color Light Bar Indicator on the top panel
- 4-way Directional-pad (D-pad) for intuitive control and operation
- Built-in GPS Receiver/Antenna for effective fleet management
- Built-in Bluetooth for hands-free operation – Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
- Optional DES and AES Encryption
- Built-in Motion Sensor (Man-down, Stationary and Motion Detection)
- IP54/55/67 and MIL-STD-810 C/D/E/F/G
- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 512 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option

- Intrinsically Safe Option (Available later)
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

### DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

### DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- Optional ARC4 Encryption
- Energy Efficient

### ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Full Keypad Model  
Standard & Basic Models



7-color Light Bar Indicator

14-pin Universal Connector offers reliable connectivity even in harsh environment with a wide-range of accessories.



### Multi-Protocol

Unsurpassed interoperability for Public Safety and Enterprise radio users with the freedom to migrate at your own pace.



### Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



### Clarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

## Accessories

## NX-3200/3300 Portable Radios

■ <b>KNB-55L/57L/78L</b> Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh)	■ <b>KSC-256K</b> Multiple Charger (6-pocket)	■ <b>KRA-25</b> High Gain Whip Antenna	■ <b>KRA-42</b> VHF/UHF Stubby Antenna	■ <b>KBH-11</b> Belt Clip (2.5")
■ <b>KNB-56N</b> Ni-MH Battery Pack (7.2 V/1400 mAh)	■ <b>KMB-30</b> Mounting Bracket (for KSC-256)	■ <b>KRA-26</b> VHF Helical Antenna	■ <b>KEP-1</b> Earphone (3.5mm)	■ <b>KPG-180P</b> OTAP Manager
■ <b>KNB-79LC*</b> Li-ion Battery Pack (7.4 V/2860 mAh, Intrinsically Safe)	■ <b>KVC-23</b> Vehicular Charger	■ <b>KRA-27</b> UHF Whip Antenna	■ <b>KMC-41D</b> Speaker Microphone (IP54/55)	■ <b>KLH-206</b> Leather Case
■ <b>KBP-5</b> Battery Case (6 AA)	■ <b>KRA-22</b> VHF Low Profile Helical Antenna	■ <b>KRA-28</b> Broadband VHF Whip Antenna	■ <b>KMC-54WD</b> Speaker Microphone (with dual-sided 2-mic for superior ANR, IP67)	■ <b>KLH-207</b> Nylon Case
■ <b>KSC-25LSK/25S</b> Rapid Charger (Li-ion Only/Tri-Chem)	■ <b>KRA-23</b> UHF Low Profile Helical Antenna	■ <b>KRA-41</b> VHF/UHF Stubby Antenna		

\* Available Later

All accessories may not be available in all markets.  
Contact an authorized Kenwood dealer for details and complete list of all accessories.

## Specifications

	NX-3200	NX-3300
<b>GENERAL</b>		
Frequency Range	136-174 MHz	400-520 MHz
Max. Channels Per Radio	Up to 1000 CH with option	
Number of Channels	512 (64 for no LCD models)	
Number of Zones	128 (4 for no LCD models)	
Channel Spacing		
Analog	12.5/15/25*/30* kHz	12.5/25* kHz
Digital	6.25kHz/12.5 kHz	6.25kHz/12.5kHz
Power Supply	7.5V DC ± 20%	
Battery Life (FDMA / TDMA) 5-5-90		
KNB-55L (1,480 mAh)	Approx. 8 hours / Approx. 9.5 hours	
KNB-56N (1,400 mAh)	Approx. 8 hours / Approx. 9 hours	
KNB-57L (2,000 mAh)	Approx. 11 hours / Approx. 13.5 hours	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±2.0 ppm	±1.0 ppm
Dimensions	(W x H x D) Projections Not Included	
Radio Only	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-55L (1,480 mAh)	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-56N (1,400 mAh)	2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)	
KNB-57L (2,000 mAh)	2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)	
Weight Radio Only		
KNB-55L (1,480 mAh)	7.8 oz (220 g)	
KNB-56N (1,400 mAh)	11.1 oz (315 g)	
KNB-57L (2,000 mAh)	14.5 oz (410 g)	
KNB-57L (2,000 mAh)	12.0 oz (340 g)	
FCC ID	K44479000	K44479100
IC Certification	282F-479000	282F-479100

\*1.25 and 30 kHz are not included in the models sold in the USA or US territories.  
Analog measurements made per TIA603. Specifications are measured according to applicable standards.  
Specifications shown are typical and subject to change without notice, due to advancements in technology.

	NX-3200	NX-3300
RECEIVER		
Sensitivity		
NXDN® 6.25 kHz Digital (3% BER)		0.20 µV
NXDN® 12.5 kHz Digital (3% BER)		0.25 µV
DMR 12.5 KHz Digital (5% BER)		0.30 µV
DMR 12.5 KHz Digital (1% BER)		0.45 µV
Analog (12dB SINAD)		0.25 µV
Selectivity		
Analog @ 12.5 kHz		65 dB
Analog @ 25 kHz		72 dB
Intermodulation		70 dB
Spurious Rejection		70 dB
Audio Distortion		3%
Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)	
TRANSMITTER		
RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W	
Spurious Emission		70 dB
FM Hum & Noise		
Analog @ 12.5 kHz		40 dB
Analog @ 25kHz		45 dB
Audio Distortion	Less than 3%	
Digital Protocol	ETSI TS 102 361-1, -2, -3	
Emission Designator	16K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.  
NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc.  
NEXEDGE® & FleetSync® are a registered trademarks of JVCKENWOOD Corporation.  
All other trademarks are the property of their respective holders.

## MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
<b>International Protection Standard</b>					
Dust & Water Protection*	IP54/55/67				

\*Radio must equip accessory cover.

# KENWOOD

### JVCKENWOOD USA Corporation

Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

### Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

[www.kenwood.com/usa](http://www.kenwood.com/usa)

### JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

[www.kenwood.com/ca](http://www.kenwood.com/ca)



ISO9001 Registered  
JVCKENWOOD Corporation

ADS#53717 Printed in USA