

DS-2CE56C0T-IT1F Datasheet

Get a Quote



Overview

HD 720p turret camera
EXIR 2.0: advanced infrared technology with 20 m IR distance
Water and dust resistant (IP66)
4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);

Specification

DS-2CE56C0T-IT1F Specification	
Camera	
Lens	Field of view: 70.9°(3.6 mm), 92°(2.8 mm), 56.7°(6 mm), 38.6°(8 mm)
Lens Mount	M12
Day & Night	ICR
Synchronization	Internal synchronization
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Effective Pixels	1296 (H) × 732 (V)
S/N Ratio	>62dB
Image Sensor	1 MP CMOS Image Sensor
Signal System	PAL/NTSC
Frame Rate	720p@25fps/720p@30fps
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30) s to 1/50,000 s
Interface	
Video Output	1 analog HD output
General	
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 V DC±15%
Power Consumption	Max. 4 W
Protection Level	IP66
IR Range	Up to 20 m
Dimensions	Φ 110 mm × 93.2 mm (4.33" × 3.67")
Weight	350 g (0.77 lb.)

Want to Buy

[Order Now](#)[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com