

MASTER RF TEST KIT

NEW

Spectrum/Cable & Antenna Analyzers

SK-SH-KIT



RF Total Coverage

Bird's Master RF Test Kit combines the best of both worlds in RF testing needs for maintaining your RF integrity.

This Master RF Test kit provides all the necessary equipment needed for field technicians and engineers for installation, troubleshooting, and maintenance of coaxial cable and antenna systems and analysis of system performance.

This comprehensive exclusive kit provides coverage with our SiteHawk™ Cable and Antenna Analyzer, SignalHawk™ Spectrum Analyzer, including a power sensor, calibration combo and all must have connection needs with an assortment of adapters, and cables all housed in an organized case.

Coverage you need with any cable & antenna installation and maintenance for wireless service providers, contractors, military, aerospace and defense, and public safety applications. Quick and easy interference analysis of cellular systems, land mobile radio systems, Wi-Fi.

Ask about our Instructor led training.



Cable & Antenna Analyzer



Spectrum Analyzer

CABLE & ANTENNA ANALYZER HIGHLIGHTS

- Wide frequency range from 1 MHz to 6 GHz.
- Test RF cables and antennas at the frequency of operation.
- Distance to Fault, return loss, cable loss
- FDR (Frequency Domain Reflectometry) measurement method results in a highly reliable assessment of the health of critical components in your system; ultimately providing a "heads-up" before a failure occurs.

SPECTRUM ANALYZER HIGHLIGHTS

- Wide frequency range between 9 kHz to 6 GHz providing real-time spectrum monitoring and analysis of RF frequency circuits.
- Predefined Measurements: Channel Power, ACPR, OBW, Phase Noise, N dB Down Bandwidth, Field Strength, FM Demodulation and more.
- View the spectrum with trace display, spectrogram display, or both.

SK-SH-KIT

Specifications



SK-6000-TC



SH-60S-TC



5017D-AV



SK-CAL-MN-C6



FH-AV-CC



4240-401



25-T-MN

SK-6000-TC CABLE & ANTENNA ANALYZER

MEASUREMENT

Frequency Range	1 MHz to 6 GHz
Frequency Resolution	1 kHz
Output Power	-10 dBm, typical
Trace Noise Magnitude (IFBW 1kHz)	0.05 dB rms
Measurement Speed	1 ms/data point
Measurement Data Points	51 to 3201
Measure Bandwidth	100 Hz to 30 kHz
Temperature Stability	0.01 dB/°F (0.02 dB/°C)
Return Loss Measurement Range	0 dB to -60 dB
Resolution	0.01 dB
VSWR Measurement Range	1.0 to 65.0
Cable Loss Measurement Range	0 dB to 30 dB
DTF Range	0 to 5000 ft (0 to 1500 m)
Corrected Directivity	> 38 dB
Maximum Input Voltage	50 V
Immunity to Interfering Signals	+13 dBm
Power Measurement	Yes

ACCURACY

Frequency Accuracy	$\pm 2.5 \times 10^{-6}$ @25 °C
Reflect Amplitude Accuracy	-15 dB to 0 dB: 0.4 dB -25 dB to -15 dB: 1.5 dB -35 dB to -25 dB: 4.0 dB

SH-60S-TC SPECTRUM ANALYZER

MEASUREMENT

Frequency Range	9 kHz to 6 GHz
Aging	± 1 ppm
Sweep Time	1.1 ms to 1600 s full span, 2.69 ms to 1600 s settable zero span
Resolution Bandwidth	10 Hz to 5 MHz in 1, 2, 3, 5, 10 steps
Second Harmonic Distortion	1.6 GHz to 70 dBc
Third Order Intercept (TOI)	+15 dBm (-10 dBm tones, 1 MHz apart, preamp off, reference level -10 dBm)
P1dB	+5 dBm nominal
Phase Noise	-95 dBc/Hz, @10 kHz (typical -97 dBc/Hz), -115 dBc/Hz, @1 MHz (typical -116 dBc/Hz)
Measurement Range	DANL to +20 dBm
Input Attenuator Range	0 to 30 dB, 1 dB step
Max Safe Input Level	Preamp Off: +30 dBm Preamp +20 dB: 0 dBm Preamp +40 dB: -20 dBm
Reference Level Range	-140 dBm to +20 dBm, -190 dBm to +70 dBm (Ref level offset: ON)
RBW Switching Uncertainty	± 0.3 dB
Input Attenuator Uncertainty	± 0.6 dB
Display Average Noise Level (DANL)	Preamp Off: 1 GHz, -129 dBm/Hz (typical -132 dBm/Hz) Preamp +20 dB: 1 GHz, -149 dBm/Hz (typical -152 dBm/Hz) Preamp +40 dB: 1 GHz, -168 dBm/Hz (typical -169 dBm/Hz) (Input terminated, detector set to positive, trace average set to 1000, span set to 50 kHz, reference level of -100 dBm, all other settings auto-coupled, 23 \pm 5 °C normalized to 1 Hz RBW)
Residual Responses	-75 dBm

ACCURACY

Frequency Span Accuracy	$\pm 1\%$
RBW Accuracy	≥ 1 MHz, $\pm 10\%$, <1 MHz, $\pm 2\%$
Amplitude Accuracy	± 1.5 dB (ATT set to 0 dB, input signal -5 to -30 dBm, detector set to positive, sensitivity set to low, RBW auto-coupled, all other settings auto-coupled, 23 \pm 5 °C. Half hour warm-up required.)
Reference Level Accuracy	≥ -60 dBm, ± 0.8 dB

5017D-AV WIDEBAND POWER SENSOR Specifications

MEASUREMENT

Frequency Range	100 MHz to 1.3 GHz
Power Measurement Range	500 mW to 500 W average, 1300 W Peak
Impedance	50 Ohms nominal
Insertion Loss	<0.05 dB
Insertion VSWR	<1.05
Directivity	28 dB up to 100 MHz 30 dB from 100 to 1300 MHz

CONNECTORS

DPM	D89 proprietary interface
PC interface (1)	RS-232, 9600 Baud, no parity, 8 data bits, 1 stop bit, D89
PC interface (2)	USB 2.0 Type B
Connector	N(f) Both

SYSTEM

Power Supply	Less than one low-power load
USB Port	7 to 18 VDC at less than 0.1 A
DC Input Connector	7 to 18 VDC at less than 0.1 A
Data Logging	Requires 5000-NG, VPM3 or Bird RF Meter App

ENVIRONMENTAL

Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-40 °C to 80 °C (-40 °F to 176 °F)

PHYSICAL

Size	4.8 in x 4.6 in x 1.3 in (122 mm x 117 mm x 35.5 mm)
Weight	1.2 lb (.27 kg)

CERTIFICATIONS

Mechanical Shock & Vibration	IAQ MIL-PRF-28800F class 3
CE	EMC EN 61326-1-2006

SK-CAL-MN-C6 CALIBRATION COMBO

MEASUREMENT

Frequency	DC to 6 GHz
Resistance	50 Ohm
Average Power	≤ 1 W
Load Return Loss	-35 dB
Load VSWR	≤ 1.025
Open Phase Deviation	≤ ± 0.6°
Short Phase Deviation	≤ ± 0.6°

INTERFACE

Connectors	N (m)
------------	-------

ENVIRONMENTAL

Operating Temperature	15 °C to 35 °C (49 °F to 95 °F)
Storage Temperature	-40 °C to 75 °C (-40 °F to 167 °F)

FH-AV-CC HARD CASE

Specifications

PHYSICAL

Size	15.27 in x 12.13 in x 6.69 in (38.8 cm x 30.8 cm x 17 cm)
Weight	4.5 lb (2.04 kg) without foam
Body	Polypropylene

CERTIFICATIONS

Compliance	IP67, MIL-STD, 810F, 512.4, Drop Tested Per MIL-STD-3010C Method 5007
-------------------	--

4240-401 ADAPTER KIT

PHYSICAL

Size	6.5 in x 4.63 in x 1.69 in (16.5 cm x 11.8 cm x 4.3 cm)
Weight	1 lb (.45 kg)
Body	Polypropylene

CONNECTORS INCLUDED

- (1) Male, (1) Female, Type N
- (1) Male, (1) Female, Type BNC
- (1) Male, (1) Female, Type TNC
- (1) Male, (1) Female, Type UHF
- (1) Male, (1) Female, Type SMA
- (5) 50 Ohm couplers

25-T-MN TERMINATION/LOAD RESISTOR

MEASUREMENT

Power Rating	25 W
Frequency	DC - 4 GHz
VSWR DC - 1 GHz	1.10:1 max
VSWR 1 GHz - 4 GHz	1.15:1 max
Impedance	50 Ohms, Nominal

ENVIRONMENTAL

Temperature Range	-40 °C to 40 °C (-40 °F to 104 °F)
--------------------------	------------------------------------

INTERFACE

Connectors	N (m)
-------------------	-------

PHYSICAL

Product Type	Dry (Convection-Cooled)
Operating Position	Any
Finish	Black Anodized
Size	4.7 in L x 2.3 in Dia (119.4 mm x 58.5 mm)
Weight	7 oz (198 g)

birdrf.com/products

The RF Experts | USA Sales : 30303 Aurora Rd, Solon, OH 44139 | www.birdrf.com
Phone: +1 440.248.1200 / 866.695.4569 [Toll Free] | Fax: +1 440.248.5426 / 866.546.4306 [Toll Free]

Bird is not responsible for omissions or errors. Specifications subject to change without notice.
©2021 Bird • Master-RF-Test-Kit-04232021

