

OVERVIEW



1. Power button	5. HDMI 1.4b
2. Card reader	6. USB 2.0
3. Headphone / microphone combo jack (3.5mm)	7. 2x USB 3.2 Gen 1
4. Power connector	

PERFORMANCE

Processor

Processor Family

AMD 3000, AMD Athlon™, or AMD Ryzen™ 3 / 5 / 7 Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD 3020e	2	2	1.2GHz	2.6GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon™ Graphics
AMD Athlon Silver 3050U	2	2	2.3GHz	3.2GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics
AMD Athlon Gold 3150U	2	4	2.4GHz	3.3GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics
AMD Ryzen 3 3250U	2	4	2.6GHz	3.5GHz	1MB L2 / 4MB L3	DDR4-2400	AMD Radeon Graphics
AMD Ryzen 5 3500U	4	8	2.1GHz	3.7GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon Vega 8 Graphics
AMD Ryzen 7 3700U	4	8	2.3GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-2400	AMD Radeon RX Vega 10 Graphics

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Home in S mode
- Windows 10 Pro 64
- FreeDOS
- No operating system

Graphics

Graphics

Graphics	Type	Memory	Key Features
AMD Radeon Graphics	Integrated	Shared	DirectX® 12
AMD Radeon Vega 8 Graphics	Integrated	Shared	DirectX 12
AMD Radeon RX Vega 10 Graphics	Integrated	Shared	DirectX 12

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 3840x2160@30Hz)

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory<sup>[1]</sup>

- Up to 8GB (8GB SO-DIMM) DDR4-2400 offering (AMD 3020e models)
- Up to 12GB (4GB soldered + 8GB SO-DIMM) DDR4-2400 offering (Athlon or Ryzen models)

Memory Slots

- One DDR4 SO-DIMM slot (AMD 3020e models)
- One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable (Athlon or Ryzen models)

Memory Type

DDR4-2400

Notes:

- 1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

- Model with 35Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
  - 2.5" HDD up to 1TB
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 512GB
- Model with 45Wh battery: one drive, 1x M.2 SSD
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 512GB

Storage Slot

- Model with 35Wh battery: one 2.5" drive slot + one M.2 slot
  - One 2.5" drive slot, supports 2.5" SATA HDD
  - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD
- Model with 45Wh battery: one M.2 slot
  - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type

Disk Type	Interface	RPM	Security
2.5" SATA HDD	SATA 6Gb/s	5.4K	-
M.2 2242 SSD	PCIe NVMe, PCIe 3.0 x2	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	-

Removable Storage

Optical

- USB external DVD burner (DVD±RW), 9.5mm high
- None

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 1.5W x2, Dolby® Audio™

Microphone

Dual array microphone

Camera<sup>[1]</sup>

- 0.3-megapixel, with privacy shutter, fixed focus
- 720p, with privacy shutter, fixed focus

Notes:

- 1. HD720p camera for AP, NA only

Battery

Battery

- Integrated Li-Polymer 35Wh battery
- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life<sup>[1]</sup>

- MobileMark® 2014: 13 hr (45Wh)
- MobileMark 2014: 9.6 hr (35Wh)

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

**Power Adapter**  
65W round tip (2-pin, wall-mount) AC adapter

DESIGN

Display

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
15.6"	HD (1366x768)	None	TN	220 nits	Anti-glare	16:9	-	-	-	-
15.6"	HD (1366x768)	Multi-touch	TN	220 nits	Anti-glare	16:9	-	-	-	-
15.6"	FHD (1920x1080)	None	TN	220 nits	Anti-glare	16:9	-	-	-	-
15.6"	FHD (1920x1080)	None	IPS	250 nits	Anti-glare	16:9	-	-	-	-

- Touchscreen**
- On-cell touch, supports 10-point touch
  - Non-touch

Notes:

1. California Electronic Waste Recycling Fee  
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

**Keyboard**  
6-row, multimedia Fn keys, numeric keypad

**Keyboard Backlight**  
No support

**Touchpad**  
Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP)

Mechanical

**Dimensions (WxDxH)**  
362.2 x 253.4 x 19.9 mm (14.26 x 9.98 x 0.78 inches)

**Weight**  
1.85 kg (4.08 lbs)

- Case Color**
- Abyss blue
  - Almond
  - Business black
  - Cherry red
  - Platinum grey

- Surface Treatment**
- IMR
  - Texture

**Case Material**

PC + ABS (top), PC + ABS (bottom)

**Notes:**

1. The system weight varies depending on configurations

**CONNECTIVITY****Network****Onboard Ethernet**

No Ethernet

**WLAN + Bluetooth®**

802.11ac 2x2 Wi-Fi + Bluetooth 5.0, M.2 card

**Ports<sup>[1]</sup>****Standard Ports<sup>[2]</sup>**

- 1x USB 2.0
- 2x USB 3.2 Gen 1
- 1x HDMI 1.4b
- 1x card reader
- 1x headphone / microphone combo jack (3.5mm)
- 1x power connector

**Notes:**

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.  
USB 2.0: 480 Mbit/s;  
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;  
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;  
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;  
Thunderbolt™ 3: 40 Gbit/s;  
FireWire 400: 400 Mbit/s;  
FireWire 800: 800 Mbit/s
2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

**SECURITY & PRIVACY****Security****Security Chip**

Firmware TPM 2.0 integrated in chipset

**Fingerprint Reader**

- Touch style fingerprint reader on power button
- No fingerprint reader

**BIOS Security**

- Administrator password
- Power-on password
- Hard disk password

**Other Security**

Camera privacy shutter

**SERVICE****Warranty****Base Warranty**

- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service

## ENVIRONMENTAL

### Operating Environment

#### Temperature<sup>[1]</sup>

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

#### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

#### Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F)

## CERTIFICATIONS

### Green Certifications

#### Green Certifications

- ErP Lot 3
- RoHS compliant



AMD



AMD



AMD



AMD



AMD



AMD