

DS-PD15AM-LM-WB
Wireless Triple Signal Detector

HIKVISION®



PD15AM is a unique two-way wireless outdoor triple signal detector with Anti-masking feature, designed to protect the outdoor areas of your property in most harsh environment and alarm before an intruder breaks in your house

- · 90°@180° adjustable coverage
- · IP65 weather resistance for outdoor application
- · Active IR anti-masking
- · Multiple enrollment methods and easy installation
- · Frequency hopping against jamming for reliable transmission

▪ Specification

Detection Performance	
Detection Method	Passive Infrared, Microwave
Detection Range	15 m
Detection Angle	90° @ 180° adjustable
Detection Zones	92
Detectable Speed	0.3 ~ 2m/s
Sensitivity	Auto, Low
White Light Filter	10000lux
Pet Immunity	40 Kg
Microwave Frequency	24 GHz(24.15 ~ 24.25 GHz)
Digital Temperature Compensation	Support
Anti-masking	Support
Adaptable Coverage	Support Pattern mask included
Feature	
Digital Processing	Tri-Signal Logic
Sealed Optics	Support
Tamper Protection	Front, Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Anti-Sway Analytics	Support
Interface	
Power Switch	Power Up Enrolling
LED Indicator	Green(Top PIR), Red(Microwave), Orange(Bottom PIR), Green+Orange(Mask), Blue(Alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1Km
Frequency Hopping	Support
Enrolling Method	Power up, Remote ID, QR Code
Electrical Characteristics	
Standard Battery Life	5 years in work status (Standalone: being triggered 20 times per day) (With camera integrated: being triggered and completely uploading captures once per day)
Power Supply	Battery Powered

Battery Type	CR123A × 5
Typical Voltage	3V
General	
Operation Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Storage Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Operation Humidity	10% to 90%
IP Rate	IP65
Dimension(W × H × D)	75 mm × 202 mm × 73 mm
Weight	600 g
Mounting Height	0.8 to 1.2 m
Mounting Method	Wall
Application Scenario	Outdoor

▪ **Available Model**

DS-PDTT15AM-LM-WB

▪ **Accessory**

▪ **Optional**

DS-PDCM15PF-IR



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

