



Activar Windo
Ve a Configuraci3n

Model Parameters

Name	C1C 720p	C1C 1080p
Model	CS-C1C-D0-1D1WFR	CS-C1C-D0-1D2WFR

Camera

Image Sensor	1/4" Progressive Scan CMOS	1/2.9" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter	Self-adaptive shutter
Lens	2.8mm, view angle:92° (Horizontal), 110° (Diagonal)	2.8mm, view angle:106° (Horizontal), 130° (Diagonal)
Lens Mount	M12	M12
Day & Night	IR-cut filter with auto-switching	IR-cut filter with auto-switching
DNR	3D DNR	3D DNR

Activa
Ve a Cc

Image

Max. Resolution	1280 x 720	1920 x 1080
Frame Rate	Max. 25fps; Self-adaptive during network transmission	Max. 20fps; Self-adaptive during network transmission

Compression

Video Compression	H.264	H.264
H.264 Type	Main profile	Main profile
Video Bit Rate	HD; Standard; Basic. Adaptive bit rate	Ultra-HD; HD; Standard. Adaptive bit rate
Auto Bit Rate	Self-adaptive	Self-adaptive
Max. Bitrate	2Mbps	2Mbps

Activar V
Ve a Config

Network

Smart Alarm	Motion detection	Motion detection
Wi-Fi Pairing	AP pairing	AP pairing
Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol	EZVIZ cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Watermark	Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Watermark

Interface

Storage	Support Micro SD card (Max. 256G)	Support Micro SD card (Max. 256G)
Power	Micro USB	Micro USB

Activar
Ve a Coni

Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11 Mbps, 11g: 54 Mbps, 11n: 72 Mbps	11b: 11 Mbps, 11g: 54 Mbps, 11n: 72 Mbps

General

Requirements	- 10 - 45°C (14 - 113°F) Humidity 95% or less (non-condensing)	- 10 - 45°C (14 - 113°F) Humidity 95% or less (non-condensing)
Power Supply	DC 5V±10%	DC 5V±10%
Power Consumption	Max. 4.0W	Max. 4.0W
IR Range	Max. 12 meters	Max. 12 meters
Product Dimensions	64mm x 64mm x 103mm	64mm x 64mm x 103mm
Packaging Dimensions	123mm x 79mm x 125.5mm	123mm x 79mm x 125.5mm
Weight	96g	96g